

## 手扶振动压路机

## Walk-behind Vibratory Rollers



本系列属小型手扶振动压路机，适用于各种道路修补和高速公路路肩、人行道、体育场和花园草坪的碾压工作，并适合于压实管道和排水管沟槽等场地的压实作业。

The walk-behind vibratory rollers are small-size vibratory roller, applied to mending and maintaining various roads, expressway shoulder, roadside walk, parking area, sports ground and garden lawn. They are especially suited for compaction of narrow areas as pipeline channel and drainage trench etc.

### 80025L 主要特点

- 采用日本罗宾汽油发动机，具有良好起动及低油耗低排放性能；
- 液压驱动装置选用萨澳公司微型泵马达一体产品，无级变速；
- 钢轮振动采用自动起振和停振装置；操纵手柄集行走、油门和振动控制为一体，操作简单方便；
- 整机结构紧凑，体积小，重量轻，可用于狭窄场地压实作业；操纵杆可折叠，转运方便。
- Japan Robin gasoline engine with excellent starting ability, low fuel consumption and low environment emission.
- Hydraulic travel device consists of Sauer drive component of integral micro-pump & motor with an infinitely variable speed.
- Drum vibration with automatic turn-on/off mechanism. Operation handle integrated with travel, engine throttle and vibration controls for simple and easy operation.
- Entire machine in compact structure and small size for compacting work of narrow sites. Foldable control bar for convenient transportation. Foldable control bar for convenient transportation.

### 8015L 主要特点

- 本系列手扶压路机采用常发CF186F立式直喷风冷柴油机，设有电起动和手拉两套起动装置，双钢轮驱动，双钢轮振动，每个钢轮设有两个刮泥板，胶轮转向，人立地面操作；（YZC1配有座椅，人在车上操作，工作舒适）。
- ChangFa CF186F inline direct-inject air-cooled engine is adopted, with both electrical and manual startup devices, driven by double-drum and double-drum vibratory. There are two mud scraping boards besides the steel wheel. The direction is changed by rubber-tires. The roller is operated by hand on the ground. (The seat is equipped in YZC1 to make operation comfortable in the roller).

### 主要技术参数

型号			80025L	8015L
工作质量	Operating mass	kg	245	770
振幅	Vibration amplitude	mm	--	0.25
振动频率	Vibration frequency	Hz	74	48
激振力	Centrifugal force	kN	8.5	12
最高行走速度	Max. travel speed	km/h	0 ~ 2.4	2.5
爬坡能力	Gradeability	%	25	25
转弯半径	Turning radius	mm	--	2700
振动轮宽度直径	Drum width	mm	455	600 × 405
轴距	Wheelbase	mm	--	470
最小离地间隙	Ground clearance	mm	--	275
柴油机型号	Diesel model		EY20D	CF186F
柴油机功率	Diesel power	kW	2.6	5.68
外形尺寸	Overall dimensions	mm	1460 × 660 × 980	2330 × 800 × 1050

因产品在不断改进，规格、说明及外观如有变动，恕不另行通知，请谅。

Since the product is improved continuously, The specification and instruction are subject to change without separate notice.